

Chrome Dark Bamboo Flooring



Specfications

Flooring groupStrand WovenPrice4.75/sq ftSpeciesMoso Bamboo aged 5-7 YearsSq ft/box16.97FinishAccuseal Ultra with aluminum oxideSurfaceIat_smoothJanka rating5342GrainStrand WovenSustainabilityScear Act Compliant. FSC®-Certified Available By Request.Nailing info18 ga cleat 1 1/2 in to 2 in Certified Available By Request.Width5-5/8 in (142 mm)Thickness9/16 in (14 mm)Wear layerStrand bamboo all the way through (no wear layer)ProfileTongue and GroovePhofile/edgesmicro bevelPlanks DescriptionSingle length planks; all planks are same dimensions	Item No	733074274373
SpeciesMoso Bamboo aged 5-7 YearsSq ft/box16.97FinishAccuseal Ultra with aluminum oxideSurfaceflat_smoothJanka rating5342GrainStrand WovenSustainabilityLacey Act Compliant. FSC®-Certified Available By Request.Nailing info18 ga cleat 1 1/2 in to 2 in to 2 inLength6 ft (1850 mm)Width5-5/8 in (142 mm)Width5-5/8 in (142 mm)Fhickness9/16 in (14 mm)Wear layerStrand bamboo all the way through (no wear layer)ProfileTongue and GroovePlanks DescriptionSingle length planks: all planks are same	Flooring group	Strand Woven
YearsSq ft/box16.97FinishAccuseal Ultra with aluminum oxideSurfaceflat_smoothJanka rating5342GrainStrand WovenSustainabilityLacey Act Compliant. FSC®-Certified Available By Request.Nailing info18 ga cleat 1 1/2 in to 2 in 6 ft (1850 mm)Width5-5/8 in (142 mm)Thickness9/16 in (14 mm)Wear layerStrand bamboo all the way through (no wear layer)ProfileTongue and GroovePlanks DescriptionSingle length planks: all planks are same	Price	4.75/sq ft
FinishAccuseal Ultra with aluminum oxideSurfaceflat_smoothJanka rating5342GrainStrand WovenSustainabilityLacey Act Compliant. FSC®-Certified Available By Request.Nailing info18 ga cleat 1 1/2 in to 2 inLength6 ft (1850 mm)Width5-5/8 in (142 mm)Thickness9/16 in (14 mm)Wear layerStrand bamboo all the way through (no wear layer)ProfileTongue and GrooveProfile/edgesmicro bevelPlanks DescriptionSingle length planks: all planks are same	Species	Ŭ
InternAccord of the functionaluminum oxideSurfaceflat_smoothJanka rating5342GrainStrand WovenSustainabilityLacey Act Compliant. FSC®-Certified Available By Request.Nailing info18 ga cleat 1 1/2 in to 2 inLength6 ft (1850 mm)Width5-5/8 in (142 mm)Thickness9/16 in (14 mm)Wear layerStrand bamboo all the way through (no wear layer)ProfileTongue and GroovePlanks DescriptionSingle length planks: all planks are same	Sq ft/box	16.97
Janka rating5342GrainStrand WovenSustainabilityLacey Act Compliant. FSC®-Certified Available By Request.Nailing info18 ga cleat 1 1/2 in to 2 inLength6 ft (1850 mm)Width5-5/8 in (142 mm)Thickness9/16 in (14 mm)Wear layerStrand bamboo all the way through (no wear layer)ProfileTongue and GrooveProfile/edgesmicro bevelPlanks DescriptionSingle length planks: all planks are same	Finish	
GrainStrand WovenSustainabilityLacey Act Compliant. FSC®-Certified Available By Request.Nailing info18 ga cleat 1 1/2 in to 2 inLength6 ft (1850 mm)Width5-5/8 in (142 mm)Thickness9/16 in (14 mm)Wear layerStrand bamboo all the way through (no wear layer)ProfileTongue and GrooveProfile/edgesmicro bevelPlanks DescriptionSingle length planks: all planks are same	Surface	flat_smooth
SustainabilityLacey Act Compliant. FSC®-Certified Available By Request.Nailing info18 ga cleat 1 1/2 in to 2 inLength6 ft (1850 mm)Width5-5/8 in (142 mm)Thickness9/16 in (14 mm)Wear layerStrand bamboo all the way through (no wear layer)ProfileTongue and GrooveProfile/edgesmicro bevelPlanks DescriptionSingle length planks: all planks are same	Janka rating	5342
FSC®-Certified Available By Request.Nailing info18 ga cleat 1 1/2 in to 2 inLength6 ft (1850 mm)Width5-5/8 in (142 mm)Thickness9/16 in (14 mm)Wear layerStrand bamboo all the way through (no wear layer)ProfileTongue and GrooveProfile/edgesmicro bevelPlanks DescriptionSingle length planks: all planks are same	Grain	Strand Woven
Length6 ft (1850 mm)Width5-5/8 in (142 mm)Thickness9/16 in (14 mm)Wear layerStrand bamboo all the way through (no wear layer)ProfileTongue and GrooveProfile/edgesmicro bevelPlanks DescriptionSingle length planks: all planks are same	Sustainability	FSC®-Certified
Width5-5/8 in (142 mm)Thickness9/16 in (14 mm)Wear layerStrand bamboo all the way through (no wear layer)ProfileTongue and GrooveProfile/edgesmicro bevelPlanks DescriptionSingle length planks: all planks are same	Nailing info	18 ga cleat 1 1/2 in to 2 in
Thickness9/16 in (14 mm)Wear layerStrand bamboo all the way through (no wear layer)ProfileTongue and GrooveProfile/edgesmicro bevelPlanks DescriptionSingle length planks: all planks are same	Length	6 ft (1850 mm)
Wear layerStrand bamboo all the way through (no wear layer)ProfileTongue and GrooveProfile/edgesmicro bevelPlanks DescriptionSingle length planks: all planks are same	Width	5-5/8 in (142 mm)
through (no wear layer)ProfileTongue and GrooveProfile/edgesmicro bevelPlanks DescriptionSingle length planks: all planks are same	Thickness	9/16 in (14 mm)
Profile/edgesmicro bevelPlanks DescriptionSingle length planks: all planks are same	Wear layer	-
Planks Description Single length planks: all planks are same	Profile	Tongue and Groove
planks are same	Profile/edges	micro bevel
	Planks Description	planks are same

Warranty	Lifetime Structural and Finish (residential)
R value	0.54
Moisture content	ASTM D4442, Oven Dry Method: 6%-10% average
SurfSlip resistanceace	Coefficient of Friction: ASTM D2394 Average; Static 0.586; Sliding 0.59
Flammability	ASTM E648: Class 1 Interior
Smoke density	ASTM E622: Max 344 flaming, 192 non-flaming
Dimensional	ASTM D1037 50/90% RH,
Stability	Linear .03, Thickness 1.52, Width .20
Coating adhesion	Classification: 5B
Acclimation period	72 hrs (7 days recommended for extra humid/dry climates)
Weight/box	52
Planks/box	6
Radiant Heat Safe	Yes
High traffic	Yes
Pet friendly	Yes
Install below grade	No
Floating installation	No
Installation	Nail Or Glue Down