

Walcott Handscraped Bamboo Flooring



Specifications

Item No	300844149737	Warranty	Lifetime Structural and Finish (residential)
Flooring group	Strand Woven	R value	0.54
Price	5.64/sq ft	Moisture content	ASTM D4442, Oven Dry Method: 6%-10% average
Species	Moso Bamboo aged 5-7 Years	SurfSlip resistance	Coefficient of Friction: ASTM D2394 Average; Static 0.586; Sliding 0.59
Sq ft/box	16.97	Flammability	ASTM E648: Class 1 Interior
Finish	Accuseal Ultra with aluminum oxide	Smoke density	ASTM E622: Max 344 flaming, 192 non-flaming
Surface	handscraped	Dimensional	ASTM D1037 50/90% RH,
Janka rating	5342	Stability	Linear .03, Thickness 1.52, Width .20
Grain	Strand Woven	Coating adhesion	Classification: 5B
Sustainability	Lacey Act Compliant. FSC®-Certified Available By Request.	Acclimation period	72 hrs (7 days recommended for extra humid/dry climates)
Nailing info	18 ga cleat 1 1/2 in to 2 in	Weight/box	52
Length	6 ft (1850 mm)	Planks/box	6
Width	5-5/8 in (142 mm)	Radiant Heat Safe	Yes
Thickness	9/16 in (14 mm)	High traffic	Yes
Wear layer	Strand bamboo all the way through (no wear layer)	Pet friendly	Yes
Profile	Tongue and Groove	Install below grade	No
Profile/edges	micro bevel	Floating installation	No
Planks Description	Single length planks: all planks are same dimensions	Installation	Nail Or Glue Down

