🤌 ambient®

Tupelo Honey Eucalyptus 5.5 in width Flooring



Specfications

Item No	742574233919	Warranty	Lifetime Structural and
Flooring group	Strand Woven		Finish (residential)
Price	6.18/sq ft	R value	0.54
Species	Lacey Act compliant Eucalyptus harvested from well-managed forests	Moisture content	ASTM D4442, Oven Dry Method: 6%-10% average
		SurfSlip resistanceace	Coefficient of Friction: ASTM D2394 Average; Static 0.586; Sliding 0.59
Sq ft/box	28.93		
Finish	Accuseal Ultra with aluminum oxide	Flammability	ASTM E648: Class 1 Interior
Surface	flat_smooth	Smoke density	ASTM E622: Max 344 flaming, 192 non-flaming
Janka rating	5300		
Grain	Strand Woven	Dimensional	ASTM D1037 50/90% RH,
Sustainability	From well managed forests	Stability	Linear .03, Thickness 1.52, Width .20
Nailing info	18 ga cleat 1 1/2 in to 2 in	Coating adhesion	Classification: 5B
Length	4 ft (1220 mm)	Acclimation period	72 hrs (7 days recommended for extra humid/dry climates)
Width	5-1/2 in (140 mm)		
Thickness	1/2 in (12 mm)	Weight/box	78
Wear layer	Strand eucalyptus all the way through (no wear layer)	Planks/box	16
		Radiant Heat Safe	No
Profile	Tongue and Groove	High traffic	Yes
Profile/edges	micro bevel	Pet friendly	No
Planks Description	Single length planks: all planks are same dimensions	Install below grade	No
		Floating installation	No
		Installation	Nail Or Glue Down