

## Edgemere Bamboo Flooring



### Specifications

<b>Item No</b>	300844149720
<b>Flooring group</b>	Strand Woven
<b>Price</b>	5.55/sq ft
<b>Species</b>	Moso Bamboo aged 5-7 Years
<b>Sq ft/box</b>	16.97
<b>Finish</b>	Accuseal Ultra with aluminum oxide
<b>Surface</b>	distressed
<b>Janka rating</b>	5342
<b>Grain</b>	Strand Woven
<b>Sustainability</b>	Lacey Act Compliant. FSC®-Certified Available By Request.
<b>Nailing info</b>	18 ga cleat 1 1/2 in to 2 in
<b>Length</b>	6 ft (1850 mm)
<b>Width</b>	5-5/8 in (142 mm)
<b>Thickness</b>	9/16 in (14 mm)
<b>Wear layer</b>	Strand bamboo all the way through (no wear layer)
<b>Profile</b>	Tongue and Groove
<b>Profile/edges</b>	micro bevel
<b>Planks Description</b>	Single length planks: all planks are same dimensions

<b>Warranty</b>	Lifetime Structural and Finish (residential)
<b>R value</b>	0.54
<b>Moisture content</b>	ASTM D4442, Oven Dry Method: 6%-10% average
<b>SurfSlip resistance</b>	Coefficient of Friction: ASTM D2394 Average; Static 0.586; Sliding 0.59
<b>Flammability</b>	ASTM E648: Class 1 Interior
<b>Smoke density</b>	ASTM E622: Max 344 flaming, 192 non-flaming
<b>Dimensional Stability</b>	ASTM D1037 50/90% RH, Linear .03, Thickness 1.52, Width .20
<b>Coating adhesion</b>	Classification: 5B
<b>Acclimation period</b>	72 hrs (7 days recommended for extra humid/dry climates)
<b>Weight/box</b>	52
<b>Planks/box</b>	6
<b>Radiant Heat Safe</b>	Yes
<b>High traffic</b>	Yes
<b>Pet friendly</b>	Yes
<b>Install below grade</b>	No
<b>Floating installation</b>	No
<b>Installation</b>	Nail Or Glue Down

