

## **Cinnamon Flooring**



## **Specfications**

| Item No            | 733074274380  |
|--------------------|---|
| Flooring group     | Strand Woven  |
| Price              | 7.31/sq ft  |
| Species            | Moso Bamboo aged 5-7<br>Years                                   |
| Sq ft/box          | 16.97   |
| Finish             | Accuseal Ultra with<br>aluminum oxide                           |
| Surface            | flat_smooth   |
| Janka rating       | 5342  |
| Grain              | Strand Woven  |
| Sustainability     | Lacey Act Compliant.<br>FSC®-Certified<br>Available By Request. |
| Nailing info       | 18 ga cleat 1 1/2 in to 2 in                                    |
| Length             | 6 ft (1850 mm)  |
| Width              | 5-5/8 in (142 mm)   |
| Thickness          | 9/16 in (14 mm)   |
| Wear layer         | Strand bamboo all the way through (no wear layer)               |
| Profile            | Tongue and Groove   |
| Profile/edges      | micro bevel   |
| Planks Description | Single length planks: all<br>planks are same<br>dimensions      |

| Warranty               | Lifetime Structural and<br>Finish (residential)                               |
|------------------------|---|
| R value                | 0.54  |
| Moisture content       | ASTM D4442, Oven Dry<br>Method: 6%-10% average                                |
| SurfSlip resistanceace | Coefficient of Friction:<br>ASTM D2394 Average;<br>Static 0.586; Sliding 0.59 |
| Flammability           | ASTM E648: Class 1<br>Interior  |
| Smoke density          | ASTM E622: Max 344<br>flaming, 192 non-flaming                                |
| Dimensional            | ASTM D1037 50/90% RH,   |
| Stability              | Linear .03, Thickness<br>1.52, Width .20                                      |
| Coating adhesion       | Classification: 5B  |
| Acclimation period     | 72 hrs (7 days<br>recommended for extra<br>humid/dry climates)                |
| Weight/box             | 52  |
| Planks/box             | 6   |
| Radiant Heat Safe      | Yes   |
| High traffic           | Yes   |
| Pet friendly           | Yes   |
| Install below grade    | No  |
| Floating installation  | No  |
| Installation           | Nail Or Glue Down   |