

Java Bamboo Flooring



Specfications

Item No	733074274472	Warra
Flooring group	Strand Woven	
Price	6.79/sq ft	R valu
Species	Moso Bamboo aged 5-7 Years	Moistu
Sq ft/box	16.97	SurfSI
Finish	Accuseal Ultra with aluminum oxide	Flamm
Surface	flat_smooth	i iaiiii
Janka rating	5342	Smoke
Grain	Strand Woven	
Sustainability	Lacey Act Compliant.	Dimen
	FSC®-Certified Available By Request.	Stabili
Nailing info	18 ga cleat 1 1/2 in to 2 in	Coatin
Length	6 ft (1850 mm)	Acclin
Width	5-5/8 in (142 mm)	
Thickness	9/16 in (14 mm)	Weigh
Wear layer	Strand bamboo all the way through (no wear layer)	Planks
Profile	Tongue and Groove	Radiar
Profile/edges	micro bevel	High t
Planks Description	Single length planks: all	Pet frie
	planks are same	Install
	dimensions	Floatir

Warranty	Lifetime Structural and Finish (residential)
R value	0.54
Moisture content	ASTM D4442, Oven Dry Method: 6%-10% average
SurfSlip resistanceace	Coefficient of Friction: ASTM D2394 Average; Static 0.586; Sliding 0.59
Flammability	ASTM E648: Class 1 Interior
Smoke density	ASTM E622: Max 344 flaming, 192 non-flaming
Dimensional	ASTM D1037 50/90% RH,
Stability	Linear .03, Thickness 1.52, Width .20
Coating adhesion	Classification: 5B
Acclimation period	72 hrs (7 days recommended for extra humid/dry climates)
Weight/box	52
Planks/box	6
Radiant Heat Safe	Yes
High traffic	Yes
Pet friendly	Yes
Install below grade	No
Floating installation	No
Installation	Nail Or Glue Down