

Natural Wide Bamboo Flooring



Specfications

Item No	733074274540	Warranty
Flooring group	Strand Woven	
Price	6.84/sq ft	R value
Species	Moso Bamboo aged 5-7 Years	Moisture cor
Sq ft/box	16.97	SurfSlip resi
Finish	Accuseal Ultra with aluminum oxide	Flammability
Surface	flat_smooth	
Janka rating	5342	Smoke dens
Grain	Strand Woven	
Sustainability	Lacey Act Compliant. FSC®-Certified Available By Request.	Dimensional Stability
Nailing info	18 ga cleat 1 1/2 in to 2 in	Coating adh
Length	6 ft (1850 mm)	Acclimation
Width	5-5/8 in (142 mm)	
Thickness	9/16 in (14 mm)	Weight/box
Wear layer	Strand bamboo all the way through (no wear layer)	Planks/box
Profile	Tongue and Groove	Radiant Heat
Profile/edges	micro bevel	High traffic
Planks Description	Single length planks: all planks are same	Pet friendly
		Install below
	dimensions	Floating inst

Warranty	Lifetime Structural and Finish (residential)
R value	0.54
Moisture content	ASTM D4442, Oven Dry Method: 6%-10% average
SurfSlip resistanceace	Coefficient of Friction: ASTM D2394 Average; Static 0.586; Sliding 0.59
Flammability	ASTM E648: Class 1 Interior
Smoke density	ASTM E622: Max 344 flaming, 192 non-flaming
Dimensional	ASTM D1037 50/90% RH,
Stability	Linear .03, Thickness 1.52, Width .20
Coating adhesion	Classification: 5B
Acclimation period	72 hrs (7 days recommended for extra humid/dry climates)
Weight/box	52
Planks/box	6
Radiant Heat Safe	Yes
High traffic	Yes
Pet friendly	Yes
Install below grade	No
Floating installation	No
Installation	Nail Or Glue Down