

Malted Ale Eucalyptus Flooring



Specifications

Item No	808857926166	Warranty	Lifetime Structural and Finish (residential)
Flooring group	Strand Woven	R value	0.54
Price	6.21/sq ft	Moisture content	ASTM D4442, Oven Dry Method: 6%-10% average
Species	Lacey Act compliant Eucalyptus harvested from well-managed forests	SurfSlip resistance	Coefficient of Friction: ASTM D2394 Average; Static 0.586; Sliding 0.59
Sq ft/box	27.31	Flammability	ASTM E648: Class 1 Interior
Finish	Accuseal Ultra with aluminum oxide	Smoke density	ASTM E622: Max 344 flaming, 192 non-flaming
Surface	flat_smooth	Dimensional	ASTM D1037 50/90% RH,
Janka rating	5300	Stability	Linear .03, Thickness 1.52, Width .20
Grain	Strand Woven	Coating adhesion	Classification: 5B
Sustainability	From well managed forests	Acclimation period	72 hrs (7 days recommended for extra humid/dry climates)
Nailing info	18 ga cleat 1 1/2 in to 2 in	Weight/box	76
Length	4 ft (1220 mm)	Planks/box	16
Width	5-1/8 in (130 mm)	Radiant Heat Safe	No
Thickness	1/2 in (12 mm)	High traffic	Yes
Wear layer	Strand eucalyptus all the way through (no wear layer)	Pet friendly	No
Profile	Tongue and Groove	Install below grade	No
Profile/edges	micro bevel	Floating installation	No
Planks Description	Single length planks: all planks are same dimensions	Installation	Nail Or Glue Down

