

Shenandoah Mist Bamboo Flooring



Specfications

Item No	808857828026	Warranty	Lifetime Structural and
Flooring group	Strand Woven		Finish (residential)
Price	7.42/sq ft	R value	0.54
Species	Moso Bamboo aged 5-7 Years	Moisture content	ASTM D4442, Oven Dry Method: 6%-10% average
Sq ft/box	16.97	SurfSlip resistanceace	Coefficient of Friction: ASTM D2394 Average;
Finish	Accuseal Ultra with aluminum oxide		Static 0.586; Sliding 0.59
Surface	flat_smooth	Flammability	ASTM E648: Class 1 Interior
Janka rating	5342	Smoke density	ASTM E622: Max 344 flaming, 192 non-flaming
Grain	Strand Woven	Dimensional	ASTM D1037 50/90% RH,
Sustainability	Lacey Act Compliant. FSC®-Certified Available By Request.	Stability	Linear .03, Thickness 1.52, Width .20
Nailing info	18 ga cleat 1 1/2 in to 2 in	Coating adhesion	Classification: 5B
Length	6 ft (1850 mm)	Acclimation period	72 hrs (7 days recommended for extra humid/dry climates)
Width	5-5/8 in (142 mm)		
Thickness	9/16 in (14 mm)	Weight/box	52
Wear layer	Strand bamboo all the way through (no wear layer)	Planks/box	6
Profile	Tongue and Groove	Radiant Heat Safe	Yes
Profile/edges	micro bevel	High traffic	Yes
Planks Description	Single length planks: all planks are same	Pet friendly	Yes
		Install below grade	No
	dimensions	Floating installation	No

Installation

Nail Or Glue Down